Data sheet

valid from: 26/08/24



JRG Gruppo di sicurezza bronzo

- Temperatura: max. 90°C
- Materiale: bronzo, EPDM, plastica
- Regolazione di fabbrica: 600 kPa (6 bar)
- Attacco: filetto maschio
- Comprende: valvola antiriflusso, valvola di sicurezza, raccordi

DN (mm)	GN (inch)	Size (inch)	JRG code	NPK	GF code	NPK	SP	weight (kg)
15	½	½	**2200.240**		**350 782 280**		1	0.600
20	¾	¾	**2200.320**		**350 782 380**		1	0.900

DN (mm)	GN (inch)	d1 R (inch)	d2 Rp (inch)	d3 G (inch)	d4 (mm)	d5 Rp (inch)	h1 (mm)	h2 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	PN (bar)	z1 (mm)	z2 (mm)
15	½	½	¾	¾	30	¼	83	38	130	45	35	25	10	61	52
20	¾	¾	1	1	30	¼	87	47	144	52	35	29	10	70	54

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com