Data sheet

valid from: 26/08/24



JUNIOR Gruppo di sicurezza bronzo

- Temperatura: max. 90°C
- Materiale: bronzo, acciaio inossidabile, EPDM, plastica
- Regolamento: riduttore di pressione 400 kPa (4 bar), valvola di sicurezza 600 kPa (6 bar)
- Attacco: filetto femmina, filetto maschio
- Comprende: filtro a maglia grossa, riduttore di pressione, valvola di sicurezza, valvola di ritegno, senza raccordi

*Fine serie con sostituzione

GN (inch)	Size (inch)	DN (mm)	JRG code	NPK	GF code	NPK	SP	weight (kg)
½	½	15	**2233.015**		**350 712 982**	**612 213**	1	1.000
¾	¾	20	**2233.020**		**350 713 082**	**612 214**	1	1.280

GN (inch)	d2 Rp (inch)	d3 G (inch)	d4 (mm)	d5 Rp (inch)	d7 (mm)	h1 (mm)	h2 (mm)	l (mm)	l1 (mm)	l2 (mm)	PN (bar)
½	¾	¾	30	¼	52	83	34	115	86	29	16
¾	1	1	30	¼	58	87	40	125	95	30	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com