
# Data sheet

valid from: 26/08/2024




## JUNIOR Groupe de sécurité, Bronze

- Température : max. 90°C
- Matériel: bronze, acier inoxydable, EPDM, plastique
- Réglage: réducteur de pression 400 kPa (4 bar), soupape de sûreté 600 kPa (6 bar)
- Raccordement: Filetage femelle, filetage mâle
- Comprenant: filtre grossier, réducteur de pression, soupape de retenue et de sûreté, raccords

*Fin de série avec remplacement

| | DN (mm) | GN (inch) | Pouces (inch) | JRG Code | CAN | GF Code | CAN | SP | Poids (kg) |
|---|---|---|---|---|---|---|---|---|---|
| * | 15 | ½ | ½ | **2230.240** | | **350 712 980** | | 1 | 1.100 |
| * | 20 | ¾ | ¾ | **2230.320** | | **350 713 080** | | 1 | 1.480 |

| | DN (mm) | GN (inch) | d1 R (inch) | d2 Rp (inch) | d3 G (inch) | d4 (mm) | d5 Rp (inch) | d7 (mm) | h1 (mm) | h2 (mm) | l (mm) | l1 (mm) | l2 (mm) | l3 (mm) | PN (bar) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| * | 15 | ½ | ½ | ¾ | ¾ | 30 | ¼ | 52 | 83 | 34 | 165 | 86 | 29 | 25 | 16 |
| * | 20 | ¾ | ¾ | ¼ | ¼ | 30 | ¼ | 58 | 87 | 40 | 182 | 95 | 30 | 29 | 16 |

| | DN (mm) | GN (inch) | z1 (mm) | z2 (mm) |
|---|---|---|---|---|
| * | 15 | ½ | 102 | 46 |
| * | 20 | ¾ | 113 | 49 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com