Data sheet

valid from: 26/08/24



JUNIOR Gruppo di sicurezza bronzo

- Temperatura: max. 90°C
- Materiale: bronzo, acciaio inossidabile, EPDM, plastica
- Regolamento: riduttore di pressione 400 kPa (4 bar), valvola di sicurezza 600 kPa (6 bar)
- Attacco: filetto femmina, filetto maschio
- Comprende: filtro a maglie grosse, riduttore di pressione, valvola di sicurezza, valvola di ritegno, raccordi

*Fine serie con sostituzione

	DN (mm)	GN (inch)	Size (inch)	JRG code	NPK	GF code	NPK	SP	weight (kg)
*	15	½	½	**2230.240**		**350 712 980**		1	1.100
*	20	¾	¾	**2230.320**		**350 713 080**		1	1.480

	DN (mm)	GN (inch)	d1 R (inch)	d2 Rp (inch)	d3 G (inch)	d4 (mm)	d5 Rp (inch)	d7 (mm)	h1 (mm)	h2 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	PN (bar)
*	15	½	½	¾	¾	30	¼	52	83	34	165	86	29	25	16
*	20	¾	¾	¼	¼	30	¼	58	87	40	182	95	30	29	16

	DN (mm)	GN (inch)	z1 (mm)	z2 (mm)
*	15	½	102	46
*	20	¾	113	49

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com