Data sheet

valid from: 27/08/24



JRG LegioStop Valvola con sede obliqua FlowFit bronzo

- Descrizione: parte superiore priva di sacche d'acqua e senza manutenzione, volantino non ascendente con indicatore ottico di posizione, sede e stelo della valvola in acciaio inossidabile
- Temperatura: max. 90°C
- Materiale: bronzo, acciaio inossidabile, EPDM, plastica
- Connessione: FlowFit

d (mm)	DN (mm)	JRG code	NPK	GF code	NPK	SP	weight (kg)
16	12	**5239.016**		**350 895 782**		1	0.512
20	15	**5239.020**		**350 895 783**		1	0.530
25	20	**5239.025**		**350 895 784**		1	0.788
32	25	**5239.032**		**350 895 785**		1	1.280
40	32	**5239.040**		**350 895 786**		1	1.880
50	40	**5239.050**		**350 895 787**		1	2.910
63	50	**5239.063**		**350 895 788**		1	4.632

d (mm)	DN (mm)	d1 (mm)	d2 G (inch)	d3 Rp (inch)	d4 (mm)	h (mm)	l1 (mm)	l2 (mm)	z1 (mm)	z2 (mm)	⎔ (mm)
16	12	16	½	¼	53	87	165	4	41	58	6
20	15	20	½	¼	53	87	170	7	43	61	6
25	20	25	¾	¼	53	105	185	-1	49	70	6
32	25	32	1	¼	60	117	210	1	55	80	6
40	32	40	1 ¼	¼	70	130	225	-2	59	92	6
50	40	50	1 ½	¼	90	148	284	15	60	102	6
63	50	63	2	¼	90	169	330	23	73	127	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com