Data sheet

valid from: 27/08/24



JRG LegioStop Valvola con sede diritta FlowFit bronzo

- Descrizione: parte superiore priva di sacche d'acqua e senza manutenzione, volantino non ascendente con indicatore ottico di posizione, sede e stelo della valvola in acciaio inossidabile
- Temperatura: max. 90°C
- Materiale: bronzo, acciaio inossidabile, EPDM, plastica
- Connessione: FlowFit

d (mm)	DN (mm)	JRG code	NPK	GF code	NPK	SP	weight (kg)
16	12	**5364.016**		**350 895 790**		1	0.422
20	15	**5364.020**		**350 895 791**		1	0.650
25	20	**5364.025**		**350 895 792**		1	1.034
32	25	**5364.032**		**350 895 793**		1	1.570

d (mm)	DN (mm)	d1 (mm)	d2 G (inch)	d4 (mm)	h (mm)	l (mm)	z (mm)
16	12	16	½	53	70	160	47
20	15	20	½	53	70	165	50
25	20	25	¾	53	79	185	60
32	25	32	1	60	89	210	68

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com