Data sheet

valid from: 25/10/24







Guarnizione per flangia EPDM/FKM
Metrico

Model:

- Per tutte le cartelle per flangia GF metrico
- Durezza: 70° Shore **EPDM**, 75° Shore **FKM**
- **EPDM**: approvato secondo DVGW W 270, KTW
- Centraggio attraverso il diametro interno cerchio fori
- Materiale dell'inserto in acciaio: carbonio
- Corpo in gomma-acciaio con anello profilato in gomma fino al d630
- Corpo gomma-acciaio ideale per grandi dimensioni (d710 - d1000)

Idonee per cartelle con diametro interno di FA

d (mm)	DN (mm)	PN (bar)	EPDM code	NPK	FKM code	NPK	weight (kg)
16	10	16	**748 440 705**		**749 440 705**		0.012
20	15	16	**748 440 706**		**749 440 706**		0.013
25	20	16	**748 440 707**		**749 440 707**		0.014
32	25	16	**748 440 708**		**749 440 708**		0.019
40	32	16	**748 440 709**		**749 440 709**		0.026
50	40	16	**748 440 710**	**474 817**	**749 440 710**		0.039
63	50	16	**748 440 711**	**474 818**	**749 440 711**		0.050
75	65	16	**748 440 712**		**749 440 712**		0.082
90	80	16	**748 440 713**	**474 821**	**749 440 713**		0.083
110	100	16	**748 440 714**	**474 822**	**749 440 714**		0.127
125	100	16	**748 440 715**	**474 822**	**749 440 715**		0.105
140	125	16	**748 440 716**	**474 823**	**749 440 716**		0.173
160 - 180	150	16	**748 440 717**	**474 824**	**749 440 717**		0.207
200	200	16	**748 440 719**	**474 865**	**749 440 719**		0.263
225	200	16	**748 440 720**	**474 865**	**749 440 720**		0.255
250	250	16	**748 440 721**	**474 866**	**749 440 721**		0.462
280	250	16	**748 440 722**	**474 866**	**749 440 722**		0.323
315	300	16	**748 440 723**	**474 867**	**749 440 723**		0.549
355	350	16	**748 440 724**		**749 440 724**		0.870
400	400	16	**748 440 725**	**474 868**	**749 440 725**		1.088
450	500	10	**748 440 726**		**749 440 726**		0.718
500	500	10	**748 440 727**		**749 440 727**		0.718
560	600	10	**748 440 728**		**749 440 728**		0.923
630	600	10	**748 440 729**		**749 440 729**		0.923
710	700	6	**748 440 730**				0.890
800	800	6	**748 440 731**				1.340
900	900	6	**748 440 732**				1.170
1000	1000	6	**748 440 733**				1.360

d (mm)	D (mm)	D1 (mm)	di FA (mm)	H (mm)	H1 (mm)
16	46	16	6 - 16	4	3
20	51	20	10 - 20	4	3
25	61	22	12 - 22	4	3
32	71	28	18 - 28	4	3
40	82	40	30 - 40	4	3
50	92	46	36 - 46	4	3
63	107	58	48 - 58	5	4
75	127	69	59 - 69	5	4
90	142	84	73 - 84	5	4
110	162	104	94 - 104	6	5
125	162	123	113 - 123	6	5
140	192	137	127 - 137	6	5
160 - 180	218	160	150 - 160	8	6
200	273	203	192 - 203	8	6
225	273	220	207 - 220	8	6
250	328	252	238 - 252	8	6

Data sheet

valid from: 25/10/24



d (mm)	D (mm)	D1 (mm)	di FA (mm)	H (mm)	H1 (mm)
280	328	274	264 - 274	8	6
315	378	306	296 - 306	8	6
355	438	355	340 - 355	10	7
400	489	400	385 - 400	10	7
450	594	403	393 - 403	10	7
500	594	447	437 - 447	10	7
560	695	494	484 - 494	10	7
630	695	555	545 - 555	10	7
710	810	712	562 - 712	6	3
800	917	813	663 - 813	6	3
900	1017	915	765 - 915	6	3
1000	1124	1016	866 - 1016	6	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com