Data sheet

valid from: 21/08/2024





Mamelons COOL-FIT 2.0 avec isolation, d32-d140

Exécution:

- PE100 SDR11 pré isolé, métrique
- Isolation en mousse GF HE
- Résistant au choc. Couleur: Noir
- Pour des connexions courtes entre les raccords COOL-FIT 2.0 Type A

d (mm)	D (mm)	SDR	PN (bar)	Code	CAN	Poids (kg)	L1 (mm)	z (mm)
32	75	11	16	**738 914 408**	**452 132**	0.072	36	121
40	90	11	16	**738 914 409**	**452 133**	0.104	40	125
50	90	11	16	**738 914 410**	**452 134**	0.136	44	133
63	110	11	16	**738 914 411**	**452 135**	0.216	48	141
75	125	11	16	**738 914 412**	**452 136**	0.313	55	155
90	140	11	16	**738 914 413**	**452 137**	0.459	62	169
110	160	11	16	**738 914 414**	**452 138**	0.712	72	189
140	200	11	16	**738 914 416**	**452 139**	1.226	90	213

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com