Data sheet

valid from: 27/05/25





COOL-FIT 4.0 Manicotto, d32-d225

Model:

- PE100 pre-isolato SDR 11 metrico
- Isolamento in schiuma GF HE
- Resistente agli urti. Colore: nero
- Raccordo elettrofusione con labbro di tenuta integrato, per una sigillatura a prova di umidità e vapore.

d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	code	NPK	peso (kg)	D1 (mm)	L (mm)	L1 (mm)	z (mm)
32	90	25	11	16	**738 913 108**	**452 112**	0.179	97	127	36	5
40	110	32	11	16	**738 913 109**	**452 113**	0.129	117	133	40	3
50	110	40	11	16	**738 913 110**	**452 114**	0.169	117	141	44	3
63	125	50	11	16	**738 913 111**	**452 115**	0.240	132	149	48	3
75	140	65	11	16	**738 913 112**	**452 116**	0.520	147	163	55	3
90	160	80	11	16	**738 913 113**	**452 117**	0.750	168	178	62	4
110	180	100	11	16	**738 913 114**	**452 118**	0.831	188	198	72	4
140	225	125	11	16	**738 913 116**	**452 119**	1.565	233	221	84	3
160	250	150	11	16	**738 913 117**	**452 121**	1.726	258	233	90	3
225	315	200	11	16	**738 913 120**	**452 122**	3.783	324	275	110	5
250	355	250	11	16	**738 913 121**		5.767	364	298	124	0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com