
Data sheet

valid from: 25/01/2025





COOL-FIT 4.0 Coude 90°
d250-d450

Exécution:

- PE100 SDR 17 pré-isolés, métrique
- Isolation en mousse GF HE
- Enveloppe externe résistante au choc. Couleur: noir
- B: Raccord à bout lisse (raccord électrosoudable nécessaire séparement)

Remarque:

Peeling of free ends necessary prior to jointing

d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	Code	CAN	Poids (kg)	L1 (mm)	z (mm)	Type
250	355	250	17	10	**738 003 121**		11.800	123	375	B
280	400	250	17	10	**738 003 122**	**452 223**	16.560	126	430	B
315	450	300	17	10	**738 003 123**	**452 224**	28.800	133	470	B
355	500	350	17	10	**738 003 124**	**452 225**	25.000	148	900	B
400	560	400	17	10	**738 003 175**	**452 226**	59.640	150	980	B
450	630	450	17	10	**738 003 176**	**452 227**	79.200	165	1070	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com