Data sheet

valid from: 25/01/25





COOL-FIT 4.0 Curva 90°, d250-450

Model:

- PE100 pre-isolato SDR 17 metrico; tubo centrale con una striscia blu
- Isolamento in schiuma GF HE
- Camicia esterna resistente agli urti. Colore: nero
- B: Raccordo a colonna con estremità libera (raccordo separato per elettrofusione necessario per l'adesione)

Note:

Peeling of free ends necessary prior to jointing

d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	code	NPK	weight (kg)	L1 (mm)	z (mm)	Type
250	355	250	17	10	**738 003 121**		11.800	123	375	B
280	400	250	17	10	**738 003 122**	**452 223**	16.560	126	430	B
315	450	300	17	10	**738 003 123**	**452 224**	28.800	133	470	B
355	500	350	17	10	**738 003 124**	**452 225**	25.000	148	900	B
400	560	400	17	10	**738 003 175**	**452 226**	59.640	150	980	B
450	630	450	17	10	**738 003 176**	**452 227**	79.200	165	1070	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com