


Data sheet


valid from: 24/01/2025











COOL-FIT 4.0 Robinet à bilee type 179
110-230 V

Exécution:

- Matériau: ABS avec collets PE100 SDR11 métriques
- Joint de la bille en PTFE
- Inserts de fixation en acier inoxydable intégrés
- Voltage 100-230V, 50-60Hz
- Plage de réglage d'usine 90°.
- Chauffage intégré, indicateur de position (ouvert/fermé/intermédiaire)
- Y compris demi-coquilles d'isolation
- Des raccords séparés Type A sont nécessaires pour l'assemblage

d (mm)	DN (mm)	PN (bar)	Valeur-kv (Δp=1 bar)	SDR	Code	CAN	Poids (kg)
32	25	10	700	11	**138 546 208**	**456 152**	2.838
40	32	10	1000	11	**138 546 209**	**456 153**	3.174
50	40	10	1600	11	**138 546 210**	**456 154**	3.452
63	50	10	3100	11	**138 546 211**	**456 155**	4.475
75	65	10	5000	11	**138 546 212**	**456 156**	7.156
90	80	10	7000	11	**138 546 213**	**456 157**	13.000

d (mm)	D (mm)	D1 (mm)	D2 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L3 (mm)	L4 (mm)	M	z (mm)	z1 (mm)	z2 (mm)
32	135	97	82	228	36	12	152	36	190	25	M6	223	76	71
40	157	117	97	240	44	15	170	40	190	45	M8	249	82	85
50	169	117	97	246	51	15	184	44	190	45	M8	271	91	89
63	204	132	117	263	64	15	227	48	190	45	M8	321	110	101
75	235	147	132	322	85	15	276	55	190	70	M8	386	125	136
90	255	168	147	357	105	15	297	62	190	70	M8	421	140	141

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com