Data sheet

valid from: 24/01/25









COOL-FIT 4.0 Kit valvola a farfalla tipo 145, elettrico

Model:

- Materiale: ABS con attacco filettato PE100 SDR11, metrico
- Tensione 100-230V, 50-60 Hz
- Campo di regolazione impostato in fabbrica 90°.
- Heating element, position feedback (Open/Close/ Middle)
- Inclusi adattatori a flangia, flange PP-Steel, bulloni e semiconduttori isolanti
- Raccordi separati di tipo A necessari per la giunzione

d (mm)	DN (mm)	PN	kv-value (Δp=1 bar) (l/min)	EPDM code	NPK	weight (kg)
110	100	10	6500	**138 567 214**	**456 258**	13.320
140	125	10	11500	**138 567 216**	**456 259**	18.650
160	150	10	16500	**138 567 217**	**456 261**	22.346
225	200	10	39600	**138 567 220**	**456 262**	36.037

d (mm)	D (mm)	D1 (mm)	D2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	z (mm)	z1 (mm)	z2 (mm)
110	310	188	168	552	72	179	122	460	104	167	190	696	320	56
140	280	233	222	670	84	172	179	475	119	173	183	830	383	64
160	358	259		720	90	179	122	535	143	203	190	895	412	72
225	409	325		776	110	179	122	580	170	210	200	996	462	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com