
Data sheet

valid from: 25/01/2025





COOL-FIT Mamelon court avec isolation, d32-d225

Exécution:

- PE100 SDR 11/17 pré-isolés, métrique
- Isolation en mousse GF HE
- Résistant au choc. Couleur: Noir
- Pour des connexions courtes entre les raccords COOL-FIT 4.0 Type A

d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	Code	CAN	Poids (kg)	L1 (mm)	z (mm)
32	90	25	11	16	**738 913 408**	**452 132**	0.126	36	151
40	110	32	11	16	**738 913 409**	**452 133**	0.188	40	155
50	110	40	11	16	**738 913 410**	**452 134**	0.226	44	163
63	125	50	11	16	**738 913 411**	**452 135**	0.328	48	171
75	140	65	11	16	**738 913 412**	**452 136**	0.447	55	185
90	160	80	11	16	**738 913 413**	**452 137**	0.631	62	199
110	180	100	11	16	**738 913 414**	**452 138**	0.929	72	219
140	225	125	11	16	**738 913 416**	**452 139**	1.101	84	243
160	250	150	17	10	**738 913 417**	**452 141**	1.576	90	255
225	315	200	17	10	**738 913 420**	**452 142**	3.254	110	295

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com