
Data sheet

valid from: 25/01/2025





COOL-FIT 4.0 Réduction
d32-d450

Exécution:

- PE100 SDR 17 pré-isolés, métrique
- Isolation en mousse GF HE
- Enveloppe externe résistante au choc. Couleur: noir
- B: Raccord à bout lisse (raccord électrosoudable nécessaire séparement)

Remarque:

Peeling of free ends necessary prior to jointing

d (mm)	d1 (mm)	D (mm)	D1 (mm)	DN (mm)	SDR	PN (bar)	Code	CAN	Poids (kg)	L (mm)	L1 (mm)	z (mm)	Type
250	225	355	315	250	17	10	**738 903 825**		2.800	123	110	332	B
280	225	400	315	250	17	10	**738 903 829**	**452 623**	4.700	126	110	335	B
280	250	450	355	250	17	10	**738 903 830**	**452 623**	5.100	133	110	365	B
315	225	450	315	300	17	10	**738 903 836**	**452 624**	7.100	126	110	340	B
315	250	450	355	300	17	10	**738 903 837**	**452 624**	7.400	133	123	365	B
315	280	450	400	300	17	10	**738 903 838**	**452 624**	6.800	133	126	365	B
355	250	500	355	350	17	10	**738 903 844**	**452 625**	8.200	148	123	390	B
355	280	500	400	350	17	10	**738 903 845**	**452 625**	7.700	148	126	390	B
355	315	500	450	350	17	10	**738 903 846**	**452 625**	8.300	148	133	390	B
400	280	560	400	400	17	10	**738 903 853**	**452 626**	9.100	150	126	415	B
400	315	560	450	400	17	10	**738 903 854**	**452 626**	11.400	150	133	420	B
400	355	560	500	400	17	10	**738 903 855**	**452 626**	11.000	150	148	405	B
450	280	630	400	450	17	10	**738 903 862**	**452 627**	13.200	165	126	390	B
450	315	630	450	450	17	10	**738 903 863**	**452 627**	13.600	165	133	390	B
450	355	630	500	450	17	10	**738 903 864**	**452 627**	13.700	165	148	393	B
450	400	630	560	450	17	10	**738 903 865**	**452 627**	14.800	165	150	395	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com