Data sheet

valid from: 21/08/2024







COOL-FIT 4.0 Raccord de transition PE/acier inoxydable
Avec écrou libre G

Exécution:

- Raccord avec bout lisse PE100 SDR11 métrique
- Acier inoxydable 1.4404 / 316L avec écrou union desserré G
- Inclus joint plat EPDM
- Y compris demi-coquilles d'isolation

d (mm)	D (mm)	Thread	Pouces (inch)	DN (mm)	SDR	PN (bar)	Code	CAN	Poids (kg)
32	104	G	½	25	11	16	**738 943 308**	**454 211**	0.250
32	104	G	¾	25	11	16	**738 943 318**	**454 212**	0.264
32	104	G	1	25	11	16	**738 943 328**	**454 213**	0.296
40	128	G	1 ¼	32	11	16	**738 943 309**	**454 215**	0.595
40	128	G	1 ½	32	11	16	**738 943 319**	**454 216**	0.655
50	138	G	1 ½	40	11	16	**738 943 310**	**454 217**	0.820
63	149	G	2	50	11	16	**738 943 311**	**454 221**	1.307

d (mm)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)
32	104	90	133	36	101	126
32	104	90	135	36	101	129
32	104	90	135	36	101	129
40	128	110	155	40	91	148
40	128	110	157	40	91	148
50	138	110	164	44	96	154
63	149	125	186	48	103	170

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com