Data sheet


valid from: 21/08/24




COOL-FIT 4.0 Raccordo di passaggio PE/acciaio inox con ghiera G

Model:

- Raccordo di testa PE100 SDR11, metrico con estremità libera
- Stainless steel 1.4404 / 316L with loose union nut G
- Con guarnizione EPDM a sede piana
- Con camicia isolante



d (mm)	D (mm)	Thread	Size (inch)	DN (mm)	SDR	PN (bar)	code	NPK	weight (kg)
32	104	G	½	25	11	16	**738 943 308**	**454 211**	0.250
32	104	G	¾	25	11	16	**738 943 318**	**454 212**	0.264
32	104	G	1	25	11	16	**738 943 328**	**454 213**	0.296
40	128	G	1 ¼	32	11	16	**738 943 309**	**454 215**	0.595
40	128	G	1 ½	32	11	16	**738 943 319**	**454 216**	0.655
50	138	G	1 ½	40	11	16	**738 943 310**	**454 217**	0.820
63	149	G	2	50	11	16	**738 943 311**	**454 221**	1.307



d (mm)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)
32	104	90	133	36	101	126
32	104	90	135	36	101	129
32	104	90	135	36	101	129
40	128	110	155	40	91	148
40	128	110	157	40	91	148
50	138	110	164	44	96	154
63	149	125	186	48	103	170

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com