
Data sheet

valid from: 25/10/24





COOL-FIT 2.0/4.0 Calotta di passaggio, PE/Ottone
Con filetto femmina Rp

Model:

- Raccordo a PE100 SDR11, metrico con estremità libera
- Ottone CuZn40Pb2 con filettatura femminile Rp
- Guarnizione: O-ring EPDM

d (mm)	Thread	Size (inch)	DN (mm)	SDR	PN (bar)	code	NPK	weight (kg)	L (mm)	L1 (mm)	L2 (mm)
32	Rp	½	25	11	16	**738 960 008**		0.200	107	36	69
40	Rp	½	32	11	16	**738 960 009**		0.210	113	40	73
50	Rp	½	40	11	16	**738 960 010**		0.250	117	44	73
63	Rp	½	50	11	16	**738 960 011**		0.300	121	48	73
75	Rp	½	65	11	16	**738 960 012**		0.400	128	55	73
90	Rp	½	80	11	16	**738 960 013**		0.476	135	62	73
110	Rp	½	100	11	16	**738 960 014**		0.695	145	72	73
140	Rp	½	125	11	16	**738 960 016**		0.954	209	84	73
160	Rp	½	150	11	16	**738 960 017**		1.300	193	90	73
225	Rp	½	200	11	16	**738 960 020**		2.532	221	110	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com