




VSH XPress Stainless ball valve high (press x thread)

XPR21001

XPress

Approvals

Assortment

Art. No	Size	Item weight	l x w x h	Packaging	GTIN
2010001011	15xG1/2 (DN10)	0.28 kg	121x122x30	Bag (1 pce)	05708537597042
2015001011	18xG3/4 (DN15)	0.34 kg	126x126x32	Bag (1 pce)	05708537597103
2020001001	22xG3/4 (DN20)	0.39 kg	127x131x40	Bag (1 pce)	05708537597165
2025001001	28xG1 (DN25)	0.75 kg	156x148x41	Bag (1 pce)	05708537597226
2032001001	35xG1 1/4 (DN32)	1.12 kg	170x159x57	Bag (1 pce)	05708537597288
2040001001	42xG1 1/2 (DN40)	1.75 kg	198x190x68	Bag (1 pce)	05708537597349
2050001001	54xG2 (DN50)	2.85 kg	216x208x85	Bag (1 pce)	05708537597400

Dimensions

Art. No	Size	L0	l1	d1	D1	z1	l2	d2	z2
2010001011	15xG1/2 (DN10)	75	47	15.3 (DN10)	23	27	38	21.3 (1/2" (DN15))	27
2015001011	18xG3/4 (DN15)	75	51.5	18.3 (DN15)	27	32	43	26.9 (3/4" (DN20))	32
2020001001	22xG3/4 (DN20)	75	60.5	22.3 (DN20)	32	40	52	26.9 (3/4" (DN20))	36
2025001001	28xG1 (DN25)	100	67.5	28.3 (DN25)	38	45	56	33.7 (1" (DN25))	37
2032001001	35xG1 1/4 (DN32)	100	80.5	35.3 (DN32)	45	55	67	42.4 (1 1/4" (DN32))	46
2040001001	42xG1 1/2 (DN40)	119	99	42.4 (DN40)	54	69	78	48.3 (1 1/2" (DN40))	57
2050001001	54xG2 (DN50)	119	113	54.4 (DN50)	65	79	96	60.3 (2" (DN50))	69

Characteristics

Colors	Silver
Materials	Stainless steel (Stainless steel 316L (1.4404))
Manufacturer	Broen
Shape	Straight
Connection type	Press (M), G - female thread gas cylindrical (BSPP)

Technical specifications

Max. operating pressure	16 bar (liquid)
Min. temperature	-35ºC
Max. temperature	135ºC

General

Category	Valves
ETIM class	EC011343 Ball valve
Intrastat code	84818081